

PondZorb

Floating Oil Removal

PondZorb quickly and effectively coagulates oil floating on water, encapsulating the petroleum hydrocarbons into a non-leachable form. The coagulated oil can then be easily removed by hand or mechanical extraction.

1. Apply PondZorb evenly to the oil on the water surface.
2. Remove the coagulated PondZorb the water.
3. Dispose spent product per local, state and federal regulations.



LBI Renewable offers a PondGun for those larger jobs. The PondGun uses compressed air to extract PondZorb from the container and disperses it over the water surface. The system requires an air compressor with 8 cfm at 90 psi output, which will push 75 pounds per minute of product.

*PondZorb meets NCP's sorbent definition in 40 CFR 300.915(g)(1)(i)(B)

Recommended Coverage Area

The coverage area will depend upon the oil thickness. For small jobs, sheen of oil to 1/16" on the surface, our 5 gallon pail will cover approximately 600 square feet. As the oil thickness increases, this area is reduced. For more than a one inch of oil on the surface, we recommend mechanical extraction prior to PondZorb use.

Available Sizes



5 gal. Buckets

55 gal. Drums

1 ton Bulk Bag

LBI Renewable

Manufacturer

Phone: 307.684.9340

Toll Free: 877.684.9340

E-mail: info@lbirenewable.com



WWW.LBIRENEWABLE.COM

MADE IN WYOMING